



16-Port, 24-Port Copper Gigabit Switches

Cost-Effectively Bringing Gigabit Connections to Desktops

Now, with the new high port-density Desktop Gigabit Switches from D-Link, upgrading your desktops to Gigabit connections has never been more cost-effective and easier. These desktop Gigabit switches offer an economical way for your workgroup to benefit from the increased bandwidth of Gigabit Ethernet.

16 to 24 Copper Gigabit Ports

Each equipped with 16 to 24 Gigabit ports, these compact desktop switches provide for fast access to servers to meet your users' increasing network load. With plug-and-play installation and copper Gigabit ports capable of connecting to your existing Cat. 5 twisted-pair cable, these devices instantly enhance your workgroup's performance without requiring you to install expensive fiber cables or to go through complex re-configuration. All ports support 10/100/1000Mbps network speed auto-sensing and full/half duplex auto-negotiation.

Full-duplex Gigabit Server Access

The Gigabit ports provide dedicated bandwidths for your desktops running at 2000Mbps full-duplex. This gives workstations bottleneck-free paths to simultaneously access server data.

IEEE 802.3x Flow Control

This function support allows your servers to directly connect to the switch for fast, reliable data transfer. At 2000Mbps

full duplex, the switch provides high-speed data pipes to your servers with minimum data transfer loss.

Auto-negotiation of MDI/MDIX Cross Over

All ports support auto-negotiation of MDI/MDIX cross over. This eliminates the need for cross over cables or uplink ports. Any port can simply plug to a server, a hub or a switch, using the usual straight-through twisted-pair cable.

Seamless Integration

These switches integrate seamlessly with your existing network equipment, be it Ethernet, Fast Ethernet or Gigabit Ethernet, dispensing you of the need to replace any hardware or software.

Plug-and-Play Installation

With 10/100/1000Mbps auto-sensing, auto-negotiation for every port, plus the ability to exist with your Cat. 5 wall wiring, network installation is a breeze. All you need to do is plug the cables to the switch, and your network is up and running in a matter of minutes.

Key Features

- Inexpensive Gigabit solution for workgroup users from desktops
- 16 or 25 10/100/1000Mbps Gigabit ports on Cat. 5 cable
- 32Gbps (16-port switch), 48Gbps (24-port switch) switching fabric capacity
- Auto MDI/MDIX cross over for all ports
- Secure store-and-forward switching scheme
- Full/half-duplex for Ethernet/Fast Ethernet speeds
- Blazing 2000Mbps full duplex for Gigabit speed
- IEEE 802.3x Flow Control
- Plug-and-play installation
- Easily installable on desktop

DGS-1016D & DGS-1024D

Technical Specifications

Gigabit Switch

Standards

- IEEE 802.3 10BASE-T Ethernet (twisted-pair copper)
- IEEE 802.3u 100BASE-TX Fast Ethernet (twisted-pair copper)
- IEEE 802.3ab 1000BASE-T Gigabit Ethernet (twisted-pair copper)
- ANSI/IEEE 802.3 NWay auto-negotiation
- IEEE 802.3x Flow Control

Number of Ports

- DGS-1016D: 16 10BASE-T/100BASE-TX/1000BASE-T ports
- DGS-1024D: 24 10BASE-T/100BASE-TX/1000BASE-T ports

Protocol

CSMA/CD

Data Transfer Rates

- Ethernet:
 - 10Mbps (half duplex)
 - 20Mbps (full duplex)
- Fast Ethernet:
 - 100Mbps (half duplex)
 - 200Mbps (full duplex)
- Gigabit Ethernet:
 - 2000Mbps (full duplex)

Topology

Star

Network Cables

- 10BASE-T:
 - UTP Cat. 3, 4, 5 (100 m max.)
 - EIA/TIA-586 100-ohm STP (100 m max.)
- 100BASE-TX, 1000BASE-T:
 - UTP Cat. 5, Cat. 5e (100 m max.)
 - EIA/TIA-568 100-ohm STP (100 m max.)

Full/half Duplex

- Full/half duplex for 10/100Mbps speeds
- Full duplex for Gigabit speed

Media Interface Exchange

Auto MDI/MDIX adjustment for all ports

LED Indicators

- Per port: 10/100Mbps speed, 1000Mbps speed
- Per port: Link/Act
- Per device: Power

Performance

Switch Capacity

- DGS-1016D: 32Gbps
- DGS-1024D: 48Gbps

Transmission Method

Store-and-forward

MAC Address Table

- DGS-1016D: 8K entries per device
- DGS-1024D: 8K entries per device

MAC Address Learning

Automatic update

Packet Filtering/Forwarding Rates (half duplex)

- Ethernet: 14,880 pps per port
- Fast Ethernet: 148,810 pps per port
- Gigabit Ethernet: 1,488,100 pps per port

RAM Buffer

- DGS-1016D: 512KBytes per device
- DGS-1024D: 512KBytes per device

Physical & Environmental

Power Supply

100 to 240 VAC, 50/60 Hz internal universal power supply

Power Consumption

- DGS-1016D: 27.5 watts (max.)
- DGS-1024D: 37.5 watts (max.)

Operating Temperature

0° to 40°C

Storage Temperature

-10° to 55°C

Humidity

5% to 95% RH non-condensing

Dimensions

- DGS-1016D: 280(W) x 180(D) x 44(H) mm (device only)
- DGS-1024D: 280(W) x 180(D) x 44(H) mm (device only)

Weight

- DGS-1016D: 1.748kg (device only)
- DGS-1024D: 1.811kg (device only)

Emission (EMI)

- FCC Class A
- CE Class A
- VCCI Class A

Safety

CSA International



CSA60950
UL 60950
IEC 60950
EN 60950

Ordering Information

Copper Gigabit Switch

DGS-1016D 16 10/100/1000BASE-T ports
DGS-1024D 24 10/100/1000BASE-T ports



Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A

Canada

Europe

Germany

France

Netherlands

Belgium

Italy

Iberia

Sweden

Norway

Denmark

Finland

Singapore

Australia

Japan

China

India

Middle East (Dubai)

Turkey

Egypt

Israel

Latin America

Brazil

South Africa

Russia

Taiwan

D-Link Corp.

TEL: 1-714-885-6000

TEL: 1-905-8295033

TEL: 44-20-8731-5555

TEL: 49-6196-77990

TEL: 33-1-30238688

TEL: 31-10-282-1445

TEL: 32(0)2-517-7111

TEL: 39-2-2900-0676

TEL: 34-93-4909770

TEL: 46-(0)8564-61900

TEL: 47-22-309075

TEL: 45-43-969040

TEL: 358-9-2707-5080

TEL: 65-6774-6233

TEL: 61-2-8899-1800

TEL: 81-3-5434-9678

TEL: 86-10-8518-2533

TEL: 91-022-652-6696

TEL: 9714-8834234

TEL: 90-212-335-2553

TEL: 202-414-4295

TEL: 972-9-9715700

TEL: 56-2-232-3185

TEL: 55-11-55039320

TEL: 27(0)1266-52165

TEL: 7-095-744-0099

TEL: 886-2-2910-2626

TEL: 886-2-2914-1600

FAX: 1-866-743-4905

FAX: 1-905-8295223

FAX: 44-20-8731-5511

FAX: 49-6196-7799300

FAX: 33-1-30238689

FAX: 31-10-282-1331

FAX: 32(0)2-517-6500

FAX: 39-2-2900-1723

FAX: 34-93-4910795

FAX: 46-(0)8564-61901

FAX: 47-22-309085

FAX: 45-43-424347

FAX: 358-9-2707-5081

FAX: 65-6774-6322

FAX: 61-2-8899-1868

FAX: 81-3-5434-9868

FAX: 86-10-8518-2250

FAX: 91-022-652-8914

FAX: 9714-8834394

FAX: 90-212-335-2500

FAX: 202-415-6704

FAX: 972-9-9715601

FAX: 56-2-232-0923

FAX: 55-11-55039321

FAX: 27(0)1266-52186

FAX: 7-095-744-0099#350

FAX: 886-2-2910-1515

FAX: 886-2-2914-6299



RECYCLABLE

Rev. 01 (Jun. 2004)